

U.S. Department of Labor

Mine Safety and Health Administration



MSHA's Small Mine Office—Serving the small mines in America

Week 14

Location: _____ Supervisor: _____

Date: _____ Time: _____ Duration: _____

1) Safety Lines

- Safety harness must be worn and attached to safety lines *wherever* a fall hazard exists
- Safety lines and harnesses must be kept clean and in good repair
- Safety lines must be securely attached
- Safety harnesses have to be adjusted to the individual
- Know how to wear your harness properly!

2) Crane Safety

- Make sure the item lifted is within the load chart capabilities
- Make sure outriggers are fully extended and pads are attached before attempting any lift
- Make a walk around inspection of crane *before* use and report any defects
- Use proper hand signals and develop hand signals for special lifting applications.
- Only one person signals the crane operator but everyone can signal a stop

3) Personal Protective Equipment- Eye Protection

- Safety glasses should be worn in all work areas at all times
- Safety glasses should be equipped with side shields
- Safety glasses that are manufactured according to ANSI Z87 standards or other suitable eye protection should be worn
- Safety glasses that double as sunglasses can help reduce glare on sunny days

Attendees:

_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Employees Comments: