

MINER Act Compliant Communication & Tracking Systems and Peripherals as of June 27, 2012

Communication System Peripherals				
Manufacturer	Model Number	Product Type	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
Mine Site Technologies	Model PED1	Cap Lamp	6D-46-0	N/A ²
Kenwood USA Corporation	TK-290, TK-390	VHF or UHF Portable Radio	23-A060002-0	Not specified ³
NL Technologies	Model GII	Cap Lamp with Messenger Circuit	23-ISA070004-0	1.2 feet (0.36 meters)
Venture Design Services, Inc.	Model TMLT Text Messaging Location Transponder	Tracking Tag and Text Messaging Device	23-A080002-0	0 feet ⁴
Motorola	HT750	VHF or UHF Portable Radio	23-A080007-0	18 feet (Models AAH25RDC9AA3_N & AAH25SDC9AA3_N) 27 feet (Model AAH25KDC9AA3_N)
SubterraCom Wireless Solutions, LLC	Model 810T	Wireless Tracking and Communication Device	23-A080014-0	Not specified ³
Hughes Supply Company	HSC RDR_02	Radio Repeater	23-A080019-0	Not specified ³
L-3 Communications	ASM100001 Accolade	Mesh Radio Handset	23-A080020-0	5 feet ⁵
Mine Site Technologies	ICCL	Integrated Communications Cap Lamp with optional TAG5 tracker	23-ISA080001-0	Not specified ³
Mine Site Technologies	ICCL	Integrated Communications Cap Lamp with Optional PED	23-ISA080002-0	N/A ²
Mine Site Technologies	ICCL	Integrated Communications Cap Lamp with optional T3100 tracker	23-ISA080004-0	Not specified ³
Active Control Technology, Inc.	Model 8035	Telephone	23-A090008-0	8 feet ⁵
Matrix Design Group	P/N: 2WC-T	Two-way Text Communicator	23-A090007-0	0 feet ⁴
American Mine Research	6210	Two-way Text Messenger	23-A090014-0	0 feet ⁴
Mine Site Technologies	Model MP70 MinePhone	Intrinsically Safe Wi-Fi Handset	23-A100006-0	14.8 inches (375 mm)

Communication System Peripherals				
Manufacturer	Model Number	Product Type	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
Becker Electronics Pty. Ltd	UFMR-100 & VFMR-100	UHF and VHF Portable Radios	23-A100010-0	6.7 ft (model UFMR-100); 32.8 ft (model VFMR-100)
Argon ST, Inc.	StrataCommTrac Model C202 Miner Communicator	Text Messaging and Tracking Device	23-A100012-0	40 inches
Matrix Design Group	P/N: 2WC-HT	Two-Way Communicator Handheld Tracker	23-A100011-0	0 feet ⁴
NL Technologies	Model Ranger Phone	Wi-Fi Phone	23-A120002-0	15.5 inches
L-3 Communications	Miner Mesh Locator (MML)	Tracking, Mesh Monitor and Emergency Status Indicating Device	23-A120003-0	8.0 feet
Innovative Wireless Technologies	Model SENTINEL Mesh Handset Permissible Portable Two-Way Radio	Portable Two-Way Radio	23-A120005-0	3.3 feet

Leaky Feeder Communication Systems				
Manufacturer	Model Number	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹	
EL-EQUIP, INC	Model VHF-1 Radio System	9B-196-0	Not specified ³	
DAC	Type RFM 2000 Radio System	9B-201-0, -1	Not specified ³	
Mine Radio Systems	Flexcom Communications Systems	9B-219-0	Not specified ³	
Varis Mine Tech.	Model IS Leaky Feeder Communication System	23-A050001-0	Not specified ³	
Tunnel Radio of America	Model UltraComm Distributed Antenna Communication System	23-A070005-0	20 feet ⁵	
Becker Electronics (PTY) LTD	Becker Leaky Feeder System	23-A080003-0	0 feet ⁴	
Minecom a division of TR Corporation Pty.	MCA 2000 UHF Leaky Feeder System	23-A090001-0	8 feet	

Leaky Feeder Communication Systems			
Manufacturer	Model Number	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
Ltd.			
Minecom a division of TR Corporation Pty. Ltd.	MCA 1000 VHF Leaky Feeder System	23-A090003-0	8 feet
Kutta Technologies, Inc.	DRUM 100S UHF/VHF Communication System	23-A110004-0	8 feet (Model 100S-U/VXXXX-U1000); 12 feet (Model 100S-U/VXXXX-V1000); 0 feet (Models 100S-U/VXXXX-U/V0040 and 100S-U/VXXXX-U/V0020)
Mine Radio Systems	Model Multicom Permissible Leaky Feeder Communication System	23-A120004-0	12 feet

Tracking Systems and Devices				
Manufacturer	Model Number	Product Type	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
Mine Site Technologies	Model TAG IV Transmitter	Tracking Tag	2G-4162-0	Not specified ³
Marco	Model PRIM Model PTT-1	Tracking Tag	23-A060001-0	Not specified ³
Matrix Design Group, LLC	Model MatrixTracker T1000 RFID Tag	Tracking Tag	23-A060003-0	0 feet ⁴
NL Technologies	Model Standalone WiFi RFID Tag	Tracking Tag	23-A070001-0	Not specified ³
Venture Design Services	MLT Mobile Location Transponder Tags	Tracking Tag	23-A070003-0	0 feet ⁴
Wholesale Mine Supply	Model i-Q8X RFID Tag	Tracking Tag	23-A070004-0	Not specified ³
Mine Radio Systems	Model TP2/ISPT	Tracking Tag	23-A070006-0	Not specified ³

Tracking Systems and Devices				
Manufacturer	Model Number	Product Type	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
American Mine Research, Inc.	Model Mine Net Tag	Tracking Tag	23-A070007-0	0 feet ⁴
NL Technologies	Model GII	Cap Lamp with Tracking Tag	23-ISA070001-0	Not specified ³
Koehler-Bright Star	Model TAG5 Tracker Tag Module	Tracking Tag	23-ISA070002-0	Not specified ³
Koehler-Bright Star	Model MultiTAG TP1 Transmitter TAG PCB Assembly	Tracking Tag	23-ISA070003-0	Not specified ³
Pyott-Boone	Model 1980 Tracking Tag	Tracking Tag	23-A080004-0	8 feet ⁵
Tunnel Radio of America	Model MineAx T1 RFID Tracking Tag	Tracking Tag	23-A080005-0	0.5 feet ⁵
Extronics Ltd.	Model iTAG100/BWH3000 Tag	Tracking Tag	23-A080006-0	8 feet ⁵
Conspec Controls	911152 Personnel Tracking Transmitter	Tracking Tag	23-A080011-0	0 feet ⁴
Mine Site Technologies	T3i-SC RFID	Tracking Tag	23-A080012-0	Not specified ³
Active Control Technology, Inc.	ActiveMine Ekahau T301	Tracking Tag	23-A080017-0	Not specified ³
Wavetrend Technologies, Inc.	Wavetrend Technologies, Inc.	Tracking Tag	23-A080018-0	Not specified ³
Becker Electronics	BEC004	Vehicle Mounted Tag	23-A090004-0	0 feet ⁴
Becker Electronics	BEC003	Helmet Mounted Tag	23-A090006-0	0 feet ⁴
L-3 Communications	Model TTURT-01 Tru-Tracker UWB	Tracking Tag	23-A090009-0	0 feet ⁴
Pyott Boone Electronics	Tracker Boss	Tracking System	23-A090011-0	5 feet
Becker Electronics	BEC002	Cap Lamp Tag	23-ISA090001-0	0 feet ⁴
Koehler-Bright Star	Model TAG 3100	Tracking Tag	23-ISA090003-0	15 feet
L-3 Communications	Model TTTR-01 Tru-Tracker Tag Reader	Reverse RFID tracking with UWB over a LF backbone	23-A090017-0	46 inches
L-3 Communications	ACCOLADE	Tracking Beacon	23-A090015-0	1.7 feet
Tunnel Radio	Model TR-MX-332 MineAx Tracking System	RFID Tracking System	23-A100002-0	12 feet
Becker Electronics	TCT1 4XX	Cap Lamp Tag	23-ISA100002-0	0 feet ⁴

<i>Tracking Systems and Devices</i>				
Manufacturer	Model Number	Product Type	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
Becker Electronics	TCT0 234 and TCT0 334	Cap Lamp Tags	23-ISA100001-0	0 feet ⁴
NL Technologies	Model GII	Cap Lamp with Reverse Tracking Circuit	23-ISA110001-0	1.2 feet (0.36 meters)
Innovative Wireless Technologies	Model SENTINEL Beacon	Tracking Beacon	23-A120001-0	3.3 feet

<i>Fixed Node-Based Communications and/or Tracking Systems</i>				
Manufacturer	Model Number	Product Type	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
NL Technologies	Digital Communications System	IEEE 802.11 mesh network over fiber System	23-A080010-0	1.1 feet ⁵
Matrix Design Group, LLC	MDG METS 2.1	RFID Miner Tracking and Text Messaging System	23-A080013-0	0 feet ⁴
American Mine Research, Inc.	MN-6000 Mine Net System	RFID Miner Tracking and Text Messaging System	23-A090013-0	0 feet ⁴
American Mine Research, Inc.	MN-6215 Dual Channel Wireless Transceiver	Wireless Transceiver for use with the MN-6000 System	23-A100001-0	0 feet ⁴
Mine Site Technologies	IMPACT	IS Communications System	23-A100003-0	14.8 inches (375 mm)
NL Technologies	Portable Access Node	IEEE 802.11 mesh network over fiber System for use with Digital Communications System	23-A100004-0	14.2 inches (360 mm)
InSet Systems, LLC	10000000AA-00	Tracking and Communication System	23-A110001-0	8 feet

Wireless Node-Based Communications and/or Tracking Systems				
Manufacturer	Model Number	Product Type	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
Venture Design Services, Inc.	MineTracer Miner Location Monitoring System	IEEE 802.15.4 Text Messaging and Tracking System	23-A080001-0	5 feet
Venture Design Services, Inc.	PWAP	Battery powered WAP for use with IEEE 802.15.4 Text Messaging and Tracking System	23-A080001-0	5 feet
L-3 Communications	ACCOLADE	Wireless Mesh Communication and Tracking System	23-A080015-0	7 feet (900 MHz antennas) 18.5 feet (450MHz antennas)
Innovative Wireless Technologies	Fixed Mesh Node, with Antenna & Battery	Fixed Mesh Node	23-ISA080005-0	18.5 feet ³ (400MHz antenna), 2.5 feet ³ (900MHz pulse antenna), and 7.5 ³ feet (original 900MHz antenna)
Active Control Technology, Inc.	ActiveMine AM1000	Wireless Mesh Communication System	23-A090002-0	18 feet
Active Control Technology, Inc.	ActiveMine AM2000	Battery Powered Node for use with the Wireless Mesh Communication System	23-A090002-0	18 feet
Rajant Corporation	WE-IS UX-2400	Breadcrumb® Portable Wireless Mesh Network Nodes	23-A090012-0	3.3 feet
Argon ST, Inc.	StrataCommTrac Model C201 Subsurface Communication Node	Wireless Mesh Communication System	23-A100008-0	40 inches; refer to approval marking for additional information
Newtrax Technologies Inc.	Network Infrastructure Device	Battery Powered Wireless Node	23-A110005-0	0 feet ⁴

Medium Frequency Systems			
Manufacturer	Model Number	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
Kutta Technologies, Inc.	DRUM 100R	23-A090010-0	32 feet
Kutta Technologies, Inc.	DRUM 100P Portable Medium Frequency Radio	23-A100009-0	6.6 feet (2 meters)
Kutta Technologies, Inc.	DRUM TTR-100 Tracking Tag Receiver	23-A110003-0	0 feet ⁴

Through-The-Earth (TTE) Systems				
Manufacturer	Model Number	Product Type	Approval No.	RFI Minimum Separation Distance between blasting circuits, explosives and detonators¹
Lockheed Martin Corporation	Model No. 03538-MCS-UP-001	MagneLink Magnetic Communication System (MCS)	23-A110002-0	10.5 feet

Note 1 – The minimum safe distance is for only one device. The combined effect of multiple RF devices must be taken into account by mine operators and documented in the Emergency Response Plan (ref. MSHA Program Policy Letter P11-V-07). Refer to manufacturer recommendations and related product conditions of use for more information.

Note 2 - This device only receives RF signals, and therefore minimum safe distances around it are not applicable. The surface antenna loop and its hazards associated with blasting circuits were not evaluated.

Note 3 - A minimum separation distance was not specified by the applicant during the MSHA approval process for this device. An approval holder should submit a Revised Approval and Modification Program (RAMP) application to modify the approval to add a minimum separation distance.

Note 4 - Any device with a minimum separation distance of 0 feet is not required to be labeled as such on the MSHA approval plate.

Note 5 - These devices have a minimum separation distance that was verified by MSHA, however, this distance may not be included on the MSHA approval plate. An approval holder may submit a RAMP application to modify the approval to add the minimum separation distance.